



## 1-140 Quarter-Turn with T-Handle Pr20.1 L18



for cutout 20.1, length 18, with cylinder

### Benefits:

- ▶ Quarter-turn with T-handle.
- ▶ RH or LH application.
- ▶ Water- and dust-tight according to IP65 DIN EN 60529.
- ▶ The quarter-turn consists of two basic components which can be combined to suit your application.
- ▶ On request parts can be assembled by DIRAK.
- ▶ A pre-assembled quarter-turn can be installed in the cutout.
- ▶ All lockable handles supplied with two keys.

### Material:

- a)
  - ▶ **T-handle:** PA, black with zinc die core or zinc die, chrome plated or black
- b)
  - ▶ **Cam:** steel, zinc plated



## Quarter-turn with T-handle, PA, black

	Part Number	Latching type	Closing	Housing length	Door-thickness	Grounding type	Installation type
a)	200-9308.00-00000	Cylinder	keyed alike DIRAK 1333	L18	max.8mm	Grounding nut	screw-on

### Additional Information:

200-9308.00-00000	With stainless dust-shutter.
-------------------	------------------------------

### Complementary Products:

b) 1-102	Cams L35/45
b) 1-262	Cam with or without ramp
c) 200-0001.00-00000	Assembling cam without o-ring
c) 200-0019.00-00000	Assembling cam 90° to handle without o-ring

